



Citizens First Fire Training  
 937-305-6369  
 Chris Kessinger chris@cfftsales.com  
 16689 State Route 28  
 Chillicothe, OH 45601

Prepared For  
 David Boone  
 Yorktown Fire Department  
 8905 West Smith Street  
 Yorktown, IN 47396

Estimate Date  
 02/06/2025

Estimate Number  
 I-2573

Description	Rate	Qty	Line Total
<b>iS320 ION Spreader</b> FEATURES Solid aluminum tool body to withstand the severe duty of fire rescue service Compact tool design allow access to tight areas other tools can't reach Gator Tips are standard and include an aggressive tooth pattern that won't slip and beveled edges don't rip sheet metal Add Extended Reach Tips (ERT) to expand the maximum spread distance from 32 to over 39 inches (812 to 993 mm) Gator Tips and ERT's utilize a push button release, so they're easy to install or remove, even with gloved hands High Intensity LED lights located in the handle for increased visibility 4-Stage pumps provide amazing speed under both loaded and unloaded conditions Center positioning of the battery offers better protection Location of the controls offers superior operator control Status LEDs offer user feedback on the tool status UL Certified, NFPA 1936 compliant Powered by a DEWALT FLEXVOLT 60 Volt battery that can be shared with other DEWALT tools Length: 38.1 inches (968 mm) Width: 11.1 inches (282 mm) Height: 11.6 inches (294 mm) Weight (excl battery): 54.3 lbs (24.6 kg) Max Spreading Distance: 31.9 inches (810 mm), 39.1 inches (993 mm) with ERT Tips Highest Spreading Force (HSF): 15,100 lbs (67.2 kN) Lowest Spreading Force (LSF): 10,530 lbs (46.9 kN) Max. Spreading Force: 39,500 lbs (175.7 kN) Highest Pulling Force (HPF): 11,500 lbs (51.1 kN) Lowest Pulling Force (LPF): 7,580 lbs (33.7 kN)	\$15,458.00	1	\$15,458.00
<b>iC750 ION Cutter</b> FEATURES Solid aluminum tool body to withstand the severe duty of fire rescue service Cutter blades and center bolt design allow access to the difficult cuts A rotating handle allows the tool to be repositioned with minimal effort High Intensity LED lights located in the handle for increased visibility Powered by a DEWALT FLEXVOLT 60 Volt battery that can be shared with other DEWALT tools Length: 33.7 inches (856 mm) Width: 8.7 inches (221 mm) Height: 11.6 inches (294mm) Weight (excl battery): 54.6 lbs (24.8 kg) Cutter Opening: 7.0 inches (178 mm) Cutter Rating: A8/B9/C7/D9/E9/F4	\$13,833.00	1	\$13,833.00
<b>KS0029-KIT</b>	\$1,252.00	1	\$1,252.00

Extended Reach Tips for ION tools

iCHRG-4FAST 4 bank DeWalt Speed Charger	\$424.00	1	\$424.00
DeWalt FLEXVOLT 60V Lithium-Ion Battery (9/3 AMP/HR) As 20V Max and 20V?60V Max FLEXVOLT batteries increase in amp hours (Ah) so do the runtime capacities	\$295.00	4	\$1,180.00
Plastix Plus Mount	\$295.00	2	\$590.00
Plastix Plus Extended Reach Tips Mount	\$180.00	1	\$180.00
FREE 24/7 tool support and loaner tool program	\$0.00	1	\$0.00
Free Professional installation	\$0.00	1	\$0.00
FREE Delivery Training	\$0.00	1	\$0.00
Trade in discount	-\$10,500.00	1	-\$10,500.00
		Subtotal	22,417.00
		Tax	0.00
		Estimate Total (USD)	\$22,417.00